

illunis XMV-2020

Product Brief

eXtreme Machine Vision

Advanced Digital Machine Vision Cameras



Description:

The XMV-2020 is a 1,600(H) x 1,200 (V) - 2M pixel digital camera used in industrial machine vision, military, and scientific market applications. Designed from the ground up with the latest technologies, this camera represents a new standard in digital imaging. The XMV-2020 offers additional features such as: full 12 bit sampling and data paths, advanced triggering and CCD readout control, built in detectors that analyze the camera's performance, image processing to remove sensor defects, and on screen tools for analyzing line/columns and text overlay. The XMV-2020 provides extreme performance at a very affordable price.

XMV-2020 Product Highlights:

Latest Generation Imagers
 80,000,000 pixels per sec.
 Industry's smallest size
 12 bit sampling and data path
 On screen text and line plots
 Smear Reduction Circuit
 Pixel / Column defect correction
 12-12 bit Look up tables
 Auto exposure and gain
 Digital gain and offset for each tap
 Analog gain and offset for each tap
 Built in detectors measure performance
 Exposure and Focus
 Tap matching
 Real time SNR
 Raster parameters
 Built In test
 Industrial and Mil derated components
 Camera control GUI
 Visual Basic Version
 Free Source code with camera
 Easy setup and control

High-Speed Digital Output using
 Camera Link Base Standard



OEM Sales and Support USA Headquarters

Address: 14700 Excelsior Blvd
 Minnetonka, MN 55345 USA
 Tel: +1-952-975-9203
 fax: +1-952-294-8308
 info@illunis.com
 www.illunis.com

XMV-2020 Specifications	
Sensor	Kodak KAI-2020
Technology	Interline Transfer CCD
Max Sensor DNR	60dB = 10 ENOB
Lens Mount	C-mount
Sensing Area	11.8 mm x 8.9 mm
Pixel Size	7.4um x 7.4um
Active Pixels	1,600 (h) x 1,200 (v)
Pixel Clock	40 Mhz / 30Mhz
Frame Rates @ 40Mhz	33.6 dual, 18.3 single tap
Output Sensitivity	31µV/e
Tap Reorder	Built In
Partial Scan	Any line to any line
Binning	Independent H & V: 1-16x
Exposure	Global Electronic Shutter
Exposure Modes	Triggered Program Exposure (TPE) Triggered Manual Exposure (TME) Triggered Double Exposure (TDE) Triggered Overlap Exposure (TOE) Free Run (FRM), Free Run Synchronized (FRS)
Exposure Resolution	Free Run: 1 Line Time, Triggered: 4-1024 pixel clocks per step
Sensor Taps	1 or 2 selectable
Gain Control	Digital .001 to 16X per tap, Analog 2-40dB, 10 bit range, Color versions have additional per color pre-gain control
Offset Control	Digital ± 4094 per tap, Analog 0-255, 8 bit range in 12 bit sample, Actively clamped per line
Power	12 VDC @ 4.7W (2 tap @ 40Mhz)
Dimensions	37mm x 57mm x 57mm with C-Mount
Weight F-Mount w/o lens	240 grams, 6.4oz
Operating Temp	0 to 50 C, less than 90% RH (Design tested -40 degrees C to +70 degrees C)
Options	CALL for special configurations including conformal coatings and custom lens mounts



eXtreme Machine Vision


Advanced Digital Machine Vision Cameras

XMV Applications

Applications for illunis cameras span from microscopic to high speed aerial imaging. Illunis cameras look for terrorists to tax cheats, finger fiducials to flat-panel defects, and all for the best price available. Here are a few applications;

- * Aerial Imaging and Reconnaissance
- * PCB, BGA and LCD Flat-Panel Inspection
- * Ophthalmic
- * Biometrics
- * Metrology
- * Traffic Management
- * Interferometry
- * Scientific imaging and microscopy
- * Portrait Photography

For more information on any illunis product including detailed specifications and options please visit our web page at www.illunis.com or email info@illunis.com or call us at the number below. illunis specializes in applying our proven intellectual property to your custom requirements at realistic NRE fees - call and find your OEM solution today.



illunis LLC
USA Sales
14700 Excelsior Blvd.
Minnetonka, MN 55345

Phone: 952.975.9203
FAX: 952.294.8308
email: info@illunis.com
web: www.illunis.com